



LIFESAVER

PSA LIFESAVER 5800 Photoelectric smoke alarm

- ✓ Sensitive to slow smouldering fires
- ✓ 240VAC with 9V battery backup
- ✓ Insect screen over smoke sensing chamber to reduce nuisance alarm

**PATENTED
NEW QUICK
SLIDE DESIGN**



Features:

- ✓ Australian design and patented
- ✓ Hinge-less surface mount base plate
- ✓ Easier and quicker to fit and install
- ✓ Extra large cable terminals for easy installation
- ✓ Multiple fixing holes to suit junction boxes and knock out for conduit entry
- ✓ Suitable for ceiling or wall mount
- ✓ Extra large Test & Hush button for easy testing. Designed for easy reach with broom handle
- ✓ 4th terminal (9V) allows operation with fire indication panel to form part of an early warning indicator system



Specifications:

Compatible with:	All PSA Lifesaver range of smoke alarms, heat alarm, strobe light and auxiliary devices, Remote test and hush plate and chip, Interconnect up to 24 units
Detection Method:	Photoelectric
Alarm Sound:	85dB at 3 metres
Low Battery Indication:	Sounds a chirp at 30-40 second intervals, in addition to red LED indicator flashing
Alarm Duration:	As long as smoke is present, unit automatically resets when smoke clears
Alarm Indication:	Flashing red LED indicator
Compliance:	Activfire listed to AS3786:1993. Australian Standards Certified Product. Australian Electrical Authority Approval
Power Requirement:	240V AC 50Hz sine wave supply. Supplied with alkaline 9Vdc battery
Rating:	80mA max per alarm



FIRE • SECURITY • INTERCOMS

psaproducts.com.au

1300 772 776

enquiry@psaproducts.com.au