

PINKERTON HOMEGUARD™

SUNSET SWITCH

SECURITY TECHNOLOGY



TECHNICAL SPECIFICATIONS

MODEL: PINCDS-20N

Power:	220V to 240V ~ 50Hz
Load:	5A max
Incandescent light:	2000W max
Halogen light:	1000W max
Fluorescent lamp:	500VA max (Uncompensated)
Adjustable LUX:	5-300 LUX
Switch Status Indication:	Red LED ON/OFF
Switch Delay:	Approximately 60 sec
Operating Temperature:	-20°C to 45°C
Environmental Protection:	IP44
Safety Requirement:	CE/TUV/EN60669-1 & EN60669-2-1

- Automatically switches lights on at dusk and off at dawn
- Adjustable LUX allows for choice of setting of desired light level for automatic operation
- Red LED allows for confirmation of light operation
- Suitable for controlling incandescent, fluorescent and discharge lights
- Time delay of 60 secs preventing operation when affected by temporary influences such as passing cars
- Easy to install



N10116

17 Millicent St, Burwood, Vic 3125 Australia

Telephone: (03) 9888 9889

Facsimile: (03) 9888 9993

e-mail: sales@psaproducts.com.au

www.psaproducts.com.au



Another Quality Product from:

PSA Products
FIRE • SECURITY • INTERCOMS



Due to our commitment to continuous improvement specifications may change without notice.